

Gas Discharge Tube

Features

- Small Size Design 3.2*2.7*4.5mm
- Voltage range: 75V-800V
- Current Handling Capability: 2.0KA@8/20μs
- Low Capacitance and insertion loss
- Fast Response and long service life
- Pb-free (RoHS compliant) package
- Moisture sensitivity level: Level 1



Application

- Communication equipment
- CATV equipment
- Test equipment
- Data lines
- Power supplies
- Telecom SLIC protection
- Broadband equipment
- ADSL equipment, including ADSL2+
- XDSL equipment
- Satellite and CATV equipment
- General telecom equipment




Electrical Characteristics

Catalog Number	DC Spark-Over voltage 100V/S	Impulse Spark-Over voltage 1KV/μs	Nom impulse discharge current 8/20±5T (60S)	Insulation Resistance(DC)	Capacitance 1MHZ<6V
KW3S2R75	75±30% V	650V	2.0KA	50V >100MΩ	<1.0pF
KW3S2R90	90±30% V	600V	2.0KA	50V >100MΩ	<1.0pF
KW3S2R150	150±20% V	600V	2.0KA	100V >100MΩ	<1.0pF
KW3S2R200	200±20% V	700V	2.0KA	100V >100MΩ	<1.0pF
KW3S2R350	350±20% V	1000V	2.0KA	100V >100MΩ	<1.0pF
KW3S2R420	420±20% V	1100V	2.0KA	100V >100MΩ	<1.0pF
KW3S2R470	470±20% V	1100V	1.5KA	100V >100MΩ	<1.0pF
KW3S2R600	600±20% V	1200V	1.5KA	100V >100MΩ	<1.0pF
KW3S2R800	800±20% V	1400V	1.5KA	100V >100MΩ	<1.0pF

Agency Approvals

Agency	Agency File Number
	E324754

Product Dimensions(mm)Recommended Soldering Pad(mm)




Note: Print solder in thickness of 0.15mm to 0.20mm

Soldering method

- W solder reflow
 - Reservoir temperature: 260°C
 - Time in reservoir: 10 seconds maximum
- Manual Soldering (not recommended)
 - Temperature: 260°C
 - Time: 30 seconds maximum



Solder reflow profile



Profile Feature	Lead(Pb) free solder
Preheat and soak	
• Temperature min.(T _{smin})	150°C
• Temperature max. (T _{smax})	200°C
• Time (T _{smin} to T _{smax}) (t _s)	60 - 120 Seconds
Average ramp up rate T _{smax} to T _p	3°C/ Second Max.
Liquidous temperature (T _L)	217°C
Time at liquidous (t _L)	60 - 150 Seconds
Peak package body temperature (T _p)	260°C
Time (t _p) within 5°C of the specified classification temperature (T _c)	30 Seconds
Average ramp-down rate (T _p to T _{smax})	6°C/ Second Max.
Time (25°C to Peak Temperature)	8 Minutes Max.

Standard Packing

Revision: B12025.02.07 www.kfuse.com



ITEM	Typical (mm)
A	3.6±0.2
B	4.6±0.2
W	12±0.3
E	1.75±0.1
F	5.5±0.05
P	8.0±0.1
P2	2.0±0.05
P0	4.0±0.1
D0	Φ 1.5±0.15
D1	Φ 1.5±0.15
T	0.3±0.1
H	2.6±0.2

Packaging type	Reel Diameters (mm)	QTY(PCS) Per Reel	QTY(PCS) Per Carton	Carton Size (mm)		
				L	W	H
Taping	330	2000	40000	410	344	350

Note: The relevant parameters of the specification are reference data, please contact the company for details, please provide the latest acknowledgment, the specification is subject to modification without notice.